


24V Power Supply With Relay (Class 2)



The Avi-on AVI-PSR20-277-24-150 power supply is a simple, low cost, class 2, 24V DC power supply for commercial and industrial lighting applications. It is designed to power up to 6 sensors in parallel. The AVI-PSR20-277-24-150 handles 120-277VAC input and outputs up to 150mA 24V DC with relay connected. Easy fixture or J-box mounting with 1/2" knockout.

Features

- 150mA 24V DC output
- · Commercial application rated
- UL Listed

Certifications

UL Certifications	
UL 244 A Plenum rated	
UL 94V-0 case	
UL/cUL listed: E341446	

Product Data		
Product Type	Class 2 output power supply	
Input	120-277VAC, 50/60Hz	
Output	24VDC, 150mA	
Max Load (Ballast)	20A @ 120-277VAC	
Max Load (Incandescent)	20A @ 120VAC	
Max Load (Motor)	1hp @ 120-240VAC	
Max No. Of Sensors	Controls up to 6 sensors in parallel	
Operating Temperature	0° C to 55°C	
Storage Temperature	-10° C to 60°C	
Relative Humidity	95% non-condensing	
Mounting	Fixture or J-box mount, 0.5" knockout	
Color	White	
Weight	4.3 oz	

ORDERING INFORMATION

Part Number	Name	Description
AVI-PSR20-277-24-150	24VDC Power Supply With Relay	Class 2, 24V Power Supply + 20A Relay

To order please contact Avi-on sales at **(877) AVION-US,** (877) 284-6687 or **prosales@avi-on.com** for information on becoming an Avi-on partner and order details.

Project	Location/ Type	
	.,,,,,	



DIAGRAMS




Figure 2. Wiring Diagram (Single Load)

Momentary Switch (optional)

Brown

